

FEP-75052IN

Specification

IEEE Standard	IEEE 802.3 10Base-T Ethernet IEEE 802.3u 100Base-TX Fast Ethernet IEEE802.3x Flow Control and Back Pressure
Switch Architecture	Back-plane (Switching Fabric): 1.0/1.2Gbps
Data Processing	Store and Forward
Flow Control	IEEE 802.3x Flow Control and Back Pressure
MAC address Table Size	1K
Packet Buffer Size	1M
Network Connector	5xRJ-45 10/100BaseT(X) auto negotiation, 5x10/100M TX port Auto MDI/MDI-X function, Full/Half duplex
Network Cable	UTP/STP above Cat.5e Cable
	EIA/TIA-568 10-ohm (100m)
	Fiber Cable (Multi-mode):50/125um,62.5/125um Fiber Cable (Single-mode): 9/125um
Protocol	CSMA/CD
LED	PW1(Power 1) – Green PW2(Power 2) – Green PW3(Power 3) – Amber RLY(Relay) – Amber
	TX/RJ-45 port: Green – LNK (Link/Active) Flashing – TX port is active
Reserve Polarity Protection	Present
Overload Current Protection	Present
Power Supply	Redundant Dual DC 12V-56V Power Input
Power Consumption	3.76W@48 VDC full load, Without POE
Alarm Relay Contact	Relay outputs with current carrying capacity of 1 A @24VDC, Relay in open circuit mode when 2 powers are connected. In short circuit mode when only one power supply is connected

Removable Terminal Block	Provide 2 Redundant power , Alarm relay contact ,6 Pin Wire range: 0.34mm ² to 2.5mm ² Solid wire (AWG):12-24/14-22 Stranded wire(AWG): 12-24/14-22 Torque:5lb-In/0.5Nm/0.56Nm Wire Strip length: 7-8mm
Operating Temperature	-40°C to 75°C
Operating Humidity	5% to 95% (Non-condensing)
Storage Temperature	-40°C to 85°C
MTBF (mean time between failure)	510,304 hrs (MIL-HDBK-217F) at 25°C
Housing	Rugged Metal ,IP30 Protection
Case Dimension (LxWxD)	142 x 36.2 x 105 mm (LxWxD)
Installation	DIN Rail and Wall Mount options included
Certificates:	
Safety	IEC EN62368-1
EMC/EMS	CE, FCC, VCCI
EMI	FCC Part 15 Subpart B Class A
EN 60068-2-6	Vibration
EN 60068-2-27	Shock
EN 60068-2-32	Free Fall



 Sales@LANshack.com | 888-568-1230