

Specification

POE-63808GIN

IEEE Standard	IEEE 802.3 10Base-T Ethernet IEEE 802.3u 100Base-TX Fast Ethernet IEEE 802.3ab 1000Base-T Gigabit Ethernet IEEE 802.3z 1000Base-X Gigabit Ethernet IEEE 802.3x Flow Control and Back Pressure, IEEE 802.3af for PoE IEEE 802.3at for PoE+
Switch Architecture	Back-plane (Switching Fabric): 16Gbps
Data Processing	Store and Forward
Flow Control	IEEE 802.3x Flow Control and Back Pressure
Jumbo Frame	9KB
MAC address Table Size	4K
Packet Buffer Size	1M
Network Connector	8 x RJ-45 10/100/1000BaseT(X) auto negotiation, Auto MDI/MDI-X function, Full/Half duplex 8 x Gigabit PoE+ 802.3at/af PSE port, 30W per port
Network Cable	UTP/STP above Cat.5e Cable
	EIA/TIA-568 10-ohm (100m)
Protocol	CSMA/CD
LED	PW1 (Green): ON - Power 1 is detected PW2 (Green): ON - Power 2 is detected RLY (Amber): ON - Connect only PW1 or PW2 OFF - Both PW1 and PW2 are connected
	TX/RJ-45 port: LNK (Link/Active) (Green): ON - TX port is detected Flashing - TX data is transmitting/receiving POE (Amber): ON - PSE is activated and PD is detected OFF - PSE is detecting PD
Reserve Polarity Protection	Present
Overload Current Protection	Present
Power Supply	Redundant Dual DC 24V-56V Power Input

Alarm Relay Contact	Relay outputs with current carrying capacity of 1 A @24VDC, Relay in open circuit mode when 2 powers are connected. Relay in short circuit mode when only one power supply is connected
PoE Power	PoE power per port 30watts. Maximum 36Watts Maximum total power 200Watts with 56VDC input, Maximum total power 120Watts with 24VDC input, Supports IEEE802.3af/at
Removable Terminal Block	Provide 2 Redundant power , Alarm relay contact, 6 Pin Wire range: 0.34mm ² to 2.5mm ² Solid wire (AWG):12-24/14-22 Stranded wire(AWG): 12-24/14-22 Torque:5lb-In/0.5Nm/0.56Nm Wire Strip length: 7-8mm
Operating Temperature	-40°C to +75°C
Operating Humidity	5% to 95% (Non-condensing)
Storage Temperature	-40°C to 85°C
MTBF (mean time between failure)	>500,000 hrs (MIL-HDBK-217F) at 25°C
Housing	Rugged Metal ,IP30 Protection
Case Dimension	142 x 42.8 x 105 mm (LxWxD)
Installation	DIN Rail and Wall Mount options included
Certifications:	
Safety	LVD (EN62368-1)
EMC	CE, FCC, EN 55032/24
EMI	CISPR 32, FCC Part 15B Class A
EMS	IEC 61000-4-2 ESD: Contact: 6KV; Air: 8KV IEC 61000-4-4 EFT: Power: 2KV; Signal: 2KV IEC 61000-4-5 Surge: Power: 2KV; Signal: 2KV
Vibration	EN 60068-2-6
Shock	EN 60068-2-27
Free Fall	EN 60068-2-32



817 S Lemon Ave
Walnut, CA 91789

Phone: 626-964-7873 Fax: 626-964-7880

www.unicomlink.com email: info@unicomlink.com

@ UNICOM 2021. UNICOM is a trademark of Unicom Electric, Inc. All rights reserved.
Specifications subject to change without notice.