



PRODUCT SPECIFICATIONS

**CONVERGENT
CONNECTIVITY
TECHNOLOGY**

CAT6ESP4

Description:	23AWG Plenum, Shielded four twisted pairs, Category 6 Horizontal Cable. Extended testing to 550 MHz
Ratings/Approvals:	NEC Article 800, UL 444 Type CMP Rating FT6, ETL Electrically Verified to ANSI/TIA/EIA 568C.2 Category 6, C(ETL)US, RoHs Compliant
Applications:	Supports all category 6 applications including Ethernet 1BASE-TX, 100BASE-VG and 155 ATM. Particularly suited for high bandwidth application such as 622 ATM, Wideband, Ethernet 1000BASE-T and emerging applications with anticipated data rates to 3.2 Gbps.

CONSTRUCTION

Conductor:	23 AWG Solid Bare Copper
Number of Conductors or Pairs:	4 Pair
Construction:	4 Pairs cabled around a pair separator (spline)
Tape:	Clear Mylar Tape
Drain:	Solid Tin Copper
Shield:	Aluminum/Polyester Tape (100% Coverage)
Jacket Material:	Flame Retardant Polyvinyl Chloride
Nominal Overall Cable Diameter:	0.305 in. (7.747 mm)
Approximate Cable Weight:	49 lb/1,000 ft.

ELECTRICAL & PHYSICAL PROPERTIES

Temperature Rating:	Installation: 0°C to 50°C Operation: -2°C to 60°C
Velocity of Propagation:	72%
Mutual Capacitance:	14 pF/ft Nominal
Capacitance Unbalance:	330 pF/ft maximum
Maximum Conductor D.C.R.:	28.6Ω/1,000 ft
Maximum D.C.R. Unbalance:	5%
Maximum Delay Skew:	45 ns/100m
Characteristic Impedance:	From 0.772 MHz - 100 MHz 100 ± 15% From 100 MHz - 250 MHz 100 ± 22% From 251 MHz - 550 MHz 100 ± 32%
Insulation Colors:	Blue paired with White/Blue Orange paired with White/Orange Green paired with White/Green Brown paired with White/Brown



Issue Date: June '15 Revision: 2

THE STRONGEST LINK IN YOUR SUPPLY CHAIN



PRODUCT SPECIFICATIONS

**CONVERGENT
CONNECTIVITY
TECHNOLOGY**

CAT6ESP4

ELECTRICAL CHARACTERISTICS

Frequency	Return Loss	Attenuation	NEXT	PS-NEXT	ELFEXT	PS-ELFEXT	ACR	PS-ACR
MHz	dB	dB(100m)	dB	dB	dB	dB	dB	dB
	Minimum	Maximum	Minimum	Minimum	Minimum	Minimum	Minimum	Minimum
1	20.0	2.0	80.3	78.3	73.8	70.8	78.3	76.3
4	23.0	3.8	71.3	69.3	61.8	58.8	67.5	65.5
10	25.0	6.0	65.3	63.3	53.8	50.8	59.3	57.3
16	25.0	7.6	62.2	60.2	49.7	46.7	54.6	52.6
20	25.0	8.5	60.8	58.8	47.8	44.8	52.3	50.3
31.25	23.6	10.7	57.9	55.9	43.9	40.9	47.2	45.2
62.5	21.5	15.4	53.4	51.4	37.9	34.9	38.0	36.0
100	20.1	19.8	50.3	48.3	33.8	30.8	30.5	28.5
200	18.0	29.0	45.8	43.8	27.8	24.8	16.8	14.9
250	17.3	32.8	44.3	42.3	25.8	22.8	11.5	9.5
300	16.8	36.4	43.1	41.1	24.3	21.3	---	---
350	16.3	39.8	42.1	40.1	22.9	19.9	---	---
400	15.9	43.0	41.3	39.3	21.8	18.8	---	---
500	14.8	49.5	40.2	38.2	20.0	17.0	---	---
550	14.4	53.1	39.5	37.5	18.9	15.9	---	---

*Values above 250 MHz are for engineering information only

Purchase at

LANshack

Sales@LANshack.com | 888-568-1230

Issue Date: June '15

Revision: 2



THE STRONGEST LINK IN YOUR SUPPLY CHAIN